TWO Side

FLOORSTANDING

Advertising Display

UD-B05



USER® SPECIAL DISPLAY

High definition picture perfect quality. Intelligent temperature control system. High-fidelity quality sound.

Easy 178 degrees viewing angles.

FUNCTIONS &.

PARAMETERS



Easy upgradable options available; Android, Windows and network.



With a fast 5ms response time, blur, ghosting and distortion will be eliminated, giving way to a perfect dynamic picture .



By using the visual extension technology (S-PVA) it will give an easy 178 degrees viewing angle. No deformed pictures and no color distortion, perfect viewing.



Our full metal shielding structure will prevent any exterior electromagnetic interference.



Our intelligent temperature control system will regulate and protect the equipment. Keeping the unit performance at peak level.



Our units are equipped with high quality digital audio outputs.



Only professional / commercial grade A+ are used for our products. High brightness and contrast ratios are the key in delivering great visible advertising.



Equipped with 3D reduction technology.

Specifications			
Screen	47"	55"	65"
Resolution	1920*1080 DPI	1920*1080 DPI	1920*1080 DPI
Display Area	1039.68(H)x584.82(V) mm	1210(H)x682(V) mm	1428.48 (H) x 803.52 (V) mm
Dot pitch	0.63mm(H)*0.63mm(V)	0.63mm(H)*0.63mm(V)	0.63mm(H)*0.63mm(V)
Viewing Angle	H178, V178	H178, V178	H178, V178
Brightness	450cd/m2	450cd/m2	450cd/m2
Contrast	5000:1	5000:1	5000:1
Colors	16.7M	16.7M	16.7M
Response time	5ms	5ms	5ms
Lifetime	≥60000 hours	≥60000 hours	≥60000 hours
Power	AC 110-240V (50/60Hz)	AC 110-240V (50/60Hz)	AC 110-240V (50/60Hz)
Power consumption	100W	100W	100W
Standby power	<3W	<3W	<3W
Working temperature	-5℃~60℃	-5℃~60℃	-5°C ~60°C
Working humidity	10%~80%	10%~80%	10%~80%
Frame	Aluminum profile	Aluminum profile	Aluminum profile
Glass	Tempered glass	Tempered glass	Tempered glass
Back frame	Wall Hanging	Wall Hanging	Wall Hanging
Product size	1850X640x80(mm)	1950x810x80 (mm)	2110x940x80.5(mm)