

# MIRROR WALLMOUNTING

## Advertising Display

UD-E01



**USER®**

**SPECIAL DISPLAY**

Creating Better Visions  
[Http://en.usersdt.com](http://en.usersdt.com)

High definition picture perfect quality.

Proximity motion sensor for fast mode detectionz

High-fidelity quality sound.

Mirror function wall advertising system

# FUNCTIONS & PARAMETERS



Easy upgradable options available; Android, Windows and network.



With a fast 5ms response time, blur, ghosting and distortion will be eliminated, giving way to a perfect dynamic picture .



By using the visual extension technology (S-PVA) it will give an easy 178 degrees viewing angle. No deformed pictures and no color distortion, perfect viewing.



Our full metal shielding structure will prevent any exterior electromagnetic interference.



Our intelligent temperature control system will regulate and protect the equipment. Keeping the unit performance at peak level.



Our units are equipped with high quality digital audio outputs.



Only professional / commercial grade A+ are used for our products. High brightness and contrast ratios are the key in delivering great visible advertising.



Advertise your promotions and keep your customer's reflection in mind! Equipped with a proximity motion sensor, the display will switch to reflection mode while still showing your adds. Be creative and impress your audience every time. This solution is perfect for all type of retail and commercial environments.

## Specifications

|                     | 32"                      | 42"                     | 47"                     |
|---------------------|--------------------------|-------------------------|-------------------------|
| Screen              | 32"                      | 42"                     | 47"                     |
| Resolution          | 1920*1080 DPI            | 1920*1080 DPI           | 1920*1080 DPI           |
| Display Area        | 700 ( H ) x 394 ( V ) mm | 930(W) x 523(H)mm       | 1039.68(H)x584.82(V)mm  |
| Dot pitch           | 0.4845(H) x 0.4845 (V)   | 0.4845(H) x 0.4845 (V)  | 0.4845(H) x 0.4845 (V)  |
| Viewing Angle       | H178, V178               | H178, V178              | H178, V178              |
| Brightness          | 450cd/m2                 | 450cd/m2                | 450cd/m2                |
| Contrast            | 5000:1                   | 5000:1                  | 5000:1                  |
| Colors              | 16.7M                    | 16.7M                   | 16.7M                   |
| Response time       | 5ms                      | 5ms                     | 5ms                     |
| Lifetime            | ≥60000 hours             | ≥60000 hours            | ≥60000 hours            |
| Power               | AC 110-240V ( 50/60Hz )  | AC 110-240V ( 50/60Hz ) | AC 110-240V ( 50/60Hz ) |
| Power consumption   | 60W                      | 60W                     | 60W                     |
| Standby power       | <3W                      | <3W                     | <3W                     |
| Working temperature | -5°C ~ 60°C              | -5°C ~ 60°C             | -5°C ~ 60°C             |
| Working humidity    | 10% ~ 80%                | 10% ~ 80%               | 10% ~ 80%               |
| Frame               | Metal plate,Right Angle  | Metal plate,Right Angle | Metal plate,Right Angle |
| Glass               | Tempered glass           | Tempered glass          | Tempered glass          |
| Back frame          | Wall Hanging             | Wall Hanging            | Wall Hanging            |
| Product size        | 760x453x60(mm)           | 993x584x60(mm)          | 1095x642x60(mm)         |